## **Weights of Raw Materials**

<u>ALUMINUM</u>		<u>SHEETROCK</u>	
.004	.056 lbs/SF	1/2"	2.0 lbs/SF
.006	.086 lbs/SF	5/8"	2.5 lbs/SF
.010	.160 lbs/SF		
.013	.190 lbs/SF	<b>INSULATION CORE</b>	
.0155	.215 lbs/SF	1 lb. EPS	.083 lbs/BF
.019	.250 lbs/SF	Urethane	.167 lbs/BF
.024	.350 lbs/SF	Perlite	
.032	.454 lbs/SF	Extruded Foam	(1.5 lbs) = 0.125 lbs/BF
.040	.560 lbs/SF	Extruded Foam	(2 lbs) = 0.167 lbs/BF
.050	.703 lbs/SF		
.063	.888 lbs/SF	<u>PLYWOOD</u>	
.080	1.131 lbs/SF	1/4"	.70 lbs.SF
.125	1.760 lbs/SF	3/8"	.95 lbs/SF
		1/2"	1.35 lbs/SF
<u>FRP</u>		5/8"	1.60 lbs/SF
.020	.125 lbs/SF	3/4"	1.95 lbs/SF
.030	.250 lbs/SF	1-1/8"	
.040	.313 lbs/SF		
.060	.500 lbs/SF	<u>STEEL</u>	
.090	.750 lbs/SF	30 Ga. (.012)	.055 lbs/SF
		29 Ga. (.015)	.612 lbs/SF
<b>WAFERBOARD</b>		26 Ga. (.019)	.775 lbs/SF
1/4"	.90 lbs/SF	24 Ga. (.024)	1.000 lbs/SF
5/16"	1.04 lbs/SF	22 Ga. (.030)	1.250 lbs/SF
3/8"	1.25 lbs/SF	20 Ga. (.036)	1.500 lbs/SF
7/16"	1.46 lbs/SF	18 Ga. (.048)	2.000 lbs/SF
1/2"	1.67 lbs/SF	16 Ga. (.060)	2.500 lbs/SF
5/8"	2.08 lbs/SF		
3/4"	2.50 lbs/SF	<u>LUMBER</u>	
		SPF 2"x4"	1.75 lbs/LF
<u>HARDBOARD</u>		SPF 2"x6"	2.63 lbs/LF
1/8" STD	.701 lbs/SF	SPF 2"x8"	3.50 lbs/LF
3/16" STD	.951 lbs/SF	TRT 1"x6"	1.95 lbs/LF
1/4" STD	1.20 lbs/SF	TRT 2"x4"	2.60 lbs/LF
		TRT 2"x6"	3.90 lbs/LF
<u>HDPE</u>		TRT 2"x8"	5.20 lbs/LF
.020	.10 lbs/SF	TRT 4"x4"	5.20 lbs/LF
.030	.16 lbs/SF		
.050	.26 lbs/SF		
.100	.51 lbs/SF		
.200	1.02 lbs/SF		